

LIGHTALK 1 (LA-60003)



Product description

With recessing box - With driver
Constant current (CC) 500 mA - 655 mm - Class I



Luminaire structure

- Die-cast aluminium housing
- Extruded aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Stainless steel frame on request
- Single cable entry, through wiring upon request
- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable for LA-60003
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear
- Recessing box is included
- Suitable for walk-over with a maximum load of 500 kg

Light symbol



AS

Product colour



00 - Stainless Steel

Technical information

Light source	18 LED
Light source type	LED
Dimming type	DALI, On/Off
Material	Stainless Steel
Weight	4.6 kg
Operating temperature	-20°C to 40°C

Luminaire	
Power	28 W
Lumen	2187 - 2566 lm
Efficacy	78 - 92 lm/W
CCT / CRI	3000K CRI80, 4000K CRI80
Drive current	500 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz



Optic	AS [27°x 60°]
Bug	B0-U5-G0
ULR	100%
ULOR	100%
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hrs)	120,000
Lifetime L80B10 (hrs)	120,000
Lifetime L80B50 (hrs)	120,000

LIGHTALK 1 (LA-60003)

Product variants

HOW TO SPECIFY

LIGA	-	LA-60003	-	500	-	AS	-	8030	-	ND	-	00
		MODEL		OUTPUT		DISTRIBUTION		CRI/CCT		DIMMING		COLOUR FINISH
		LA-60003		500 28W		AS		8030		ND		00 STAINLESS STEEL
								8040		DALI		



MOUNTING DETAIL

Accessories



Connector IP68
LIGA-A62591