

RADO 1 (RA-40531)



Product description

With recessing box



Luminaire structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear

Light symbol



G

Product colour



01- Black (RAL 9011) 02- Dark Grey (RAL 7043) 03- White (RAL 9003) 05- Matt Silver (RAL 9006)



06- Bronze (RAL 6014)

Special finishes upon request



SU01- Concrete Urban SU02- Softscape Urban SU03- Stone Urban SU04- Corten Urban



SW01- OAK Woodland SW02- Walnut Woodland SW03- PINE Woodland

Technical information

Light source	1 COB
Light source type	COB
Dimming type	On/Off
Material	Aluminium
Weight	1.0 kg
Operating temperature	-20°C to 40°C

Luminaire	
Power	4 W
Lumen	124 - 133 lm
Efficacy	31 - 33 lm/W
CCT / CRI	3000K CRI80, 4000K CRI80
Drive current	350 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz




Optic	G [36°x50°]
Bug	B0-U2-G0
ULR	23.11%
ULOR	23.11%
CIE flux code n°3	87
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hrs)	50,000

RADO 1 (RA-40531)

Product variants

HOW TO SPECIFY

LIGA	-	RA-40531	-	350	-	G	-	8030	-	ND	-	01
MODEL	OUTPUT	DISTRIBUTION	CRI/CCT	DIMMING	COLOUR FINISH							
RA-40531	350 4W	G	8030	ND	01 BLACK							
			8040		02 DARK GREY							
					03 WHITE							
					05 MATT SILVER							
					06 BRONZE							
					S - SPECIAL FINISH							



RECESSING BOX