



## **Product description**

Ø186 - 288 mm - Down (Optic) & Up (Optic 2nd) - Round



#### Luminaire structure

- Die-cast aluminium housing and frame
- Pre-treated before powder coating
- ensuring high corrosion resistance
- Single cable entry

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency optical reflector

#### wiring or conduit connection when wiring


from behind is not possible

- Integral control gear

# Light symbol



## Product colour



## Special finishes upon request

- Optional surface mounting box for easy



## **Technical information**

Light source	1 & 1 COB		
Light source type	СОВ		
Dimming type	DALI, On/Off		
Material	Aluminium		
Weight	6.4 kg		
Operating temperature	-20°C to 40°C		

Luminaire	
Power	58 W
Lumen	5070 - 5132 lm
Efficacy	87 - 88 lm/W
CCT / CRI	3000K CRI80, 4000K CRI80
Drive current	700 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	AS [46°x56°]	
Optic (Up)	AS [46°x56°]	
MacAdam Ellipse	3 SDCM	
Lifetime L90B10 (hrs)	55,000	







### **Product variants**

#### HOW TO SPECIFY

liga	- TA-31883	- 700 -	AS - AS	- 8030	- ND -	01
	MODEL	OUTPUT	DISTRIBUTION	CRI/CCT	DIMMING	COLOUR FINISH
			DOWN- UP			
	TA-31883	700 58W	AS AS	8030	ND	01 BLACK
				8040	DALI	02 DARK GREY
						03 WHITE
						05 MATT SILVER
						06 BRONZE
						S - SPECIAL FINISH

86





Mounting detail

### Accessories



Surface mounting box for easy cabling (TANGO 31) LIGA-SCE-TANGO-31

We reserve the right to make technical and design changes. JULY 2023 LIGMAN AUSTRALIA 39 Tinning Street, Brunswick Victoria 3056 Telephone (03) 9222 5522 sales@ligmanaustralia.com.au www.ligmanaustralia.com.au